

Innovation create new HMI vision




mTV Machine TV Interface

Breaking through the architecture of HMI, we freed HMI from its traditional combination of LCD panel and touch screen. The compact mTV can connect various sized TVs or monitors with HDMI interface. This makes real-time display clearer and less limited.

- HD 720p High Resolution HDMI Output
- One Gigabit Ethernet Port
- Compact Design and DIN-rail Mountable
- Built-in 256MB Flash Memory
- SD Card Slot for Extension of Storage
- One USB Host Port
- Fan-less Cooling System
- Supports MPI 187.5K
- Power Isolator Inside

Traditional Architecture



HMI Large touch screen
Real-time on-site monitoring




Wider vision

TV Any Size
Real-time on-site monitoring



mTV
(HDMI interface)


mTV Architecture



mTV-100

Machine TV Interface

Dimensions



Specification

Memory	Storage(MB)	256
	RAM (MB)	256
Processor		ARM Cortex A8 600Mhz
I/O Port	SD Card Slot	SD/SDHC
	USB Host	USB 2.0 x 1
	USB Client	N/A
	Ethernet	10/100/1G x 1
	COM Port	COM1 RS-232, COM2 RS-485 2W/4W, COM3 RS-485 2W
	CAN Bus	N/A
	HDMI	Resolution 1280 x 720
RTC		Built-in (CR1225 3V lithium battery)
Power	Input Power	24±20%VDC
	Power Consumption	230mA@24V
	Power Isolation	Built In
	Voltage Resistance	500VAC (1 min)
	Isolation Resistance	Exceed 50MΩ at 500VDC
	Vibration Endurance	10 to 25Hz(X, Y, Z direction 2G 30 minutes)
Specification	Enclosure	Plastic
	Dimensions WxHxD	130 x 115 x 27mm
	Weight (kg)	Approx. 0.18 kg
	Mount	35mm Din rail mounting
	Storage Temperature	-20° ~ 70°C (-4° ~ 158°F)
	Operating Temperature	-20° ~ 55°C (-4° ~ 131°F)
	Relative Humidity	10% ~ 90% RH (non-condensing)
Certificate		Complies with CE
Software		EasyBuilder Pro V3.00.02 or later versions
Ordering Information	mTV-100	FLC014200 • HDMI to DVI cable Length=200cm
		FLC012200 • HDMI to HDMI cable Length=200cm



WEINTEK LABS., INC.
Address: 9F., No.910, Zhongzheng Rd., Zhonghe
Dist., New Taipei City 23586, Taiwan

Website: www.weintek.com
Sales: salesmail@weintek.com
Product Support: servicemail@weintek.com

Tel: +886-2-22286770
Fax: +886-2-22286771